



Vert.kurv.	-10‰		Rv = 250		-100‰										Rv = 250		0‰				Rv = 250		100‰			
Hor.kurv.					R = 25										R = -15		R = 33.25		R = -16.5				R = -16.5		R = -415	
Breddeutv.																										
Tverrfall (1% = 1mm)																										
V.kj.b.k	3%																									
H.kj.b.k	3%																									
Profil h.	52.20	52.10	51.75	51.00	50.00	49.00	48.00	47.00	46.00	45.00	44.00	43.00	42.00	41.01	40.31	40.01	40.00	40.00	40.00	40.01	40.31	41.01	42.00	42.24		
Terreng h.	52.23	52.10	51.88	50.58	49.93	48.71	47.41	46.11	43.03	40.92	39.82	39.05	39.34	39.33	38.99	39.04	38.24	38.01	38.01	37.73	37.73	39.19	41.39	41.92		
Overbyggn.	24 cm											24 cm														

Vacuri AS
Gangveg Tibben-Stemmegardshaugane
 Lengdeprofil

HOLON

Tegnet av	Saksbehandler
Sidemannskont.	JEV
Dato	Prosjektansvarlig
Prosj.nr.	Målestokk
5	1: 1000
Tegn.nr.	1: 200
1	Rev.